

AC104-M12A Series

Multipurpose Accelerometer, Side Exit 4 Pin M12 Connector, 100 mV/g, $\pm 10\%$



VIBRATION ANALYSIS HARDWARE




Product Features

Affordably Priced, Hermetically Sealed Sensors
Perfect for Thousands of Applications

- ▶ 100 mV/g Sensitivity
- ▶ ± 80 g, peak Dynamic Range
- ▶ Common M12 Connection

AC104-M12A 4 Pin Connector

Connector Pin	Polarity
1	(+) Signal/Power
2	(-) Common
3	Not Used
4	Not Used



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC104-M12A	M/AC104-M12A	Environmental		
Sensitivity ($\pm 10\%$)	100 mV/g		Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (± 3 dB)	30-600,000 CPM	0,5-10000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response ($\pm 10\%$)	120-420,000 CPM	2,0-7000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 80 g, peak *Vsource ≥ 22 V, 12Vbias		Sealing	Welded, Hermetic	
Electrical			SIL Rating	SIL 2	
Settling Time	<2.5 seconds		Physical		
Voltage Source (IEPE)	18-30 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-10 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	14 μ g/ \sqrt Hz		Weight	5.1 oz	145 grams
Spectral Noise @ 100 Hz	2.3 μ g/ \sqrt Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	2 μ g/ \sqrt Hz		Connector (Non-Integral)	4 Pin M12	
Output Impedance	<100 ohm		Resonant Frequency	1,320,000 CPM	22000 Hz
Bias Output Voltage	10-14 VDC		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Case Isolation	$>10^8$ ohm		Mounting Hardware Supplied	1/4-28 Captive	M6x1 Captive