

# AC314 Series

Low Voltage Accelerometer, Side Exit 3 Pin Connector, 25 mV/g, ±10%



VIBRATION ANALYSIS HARDWARE



## Product Features


Ultra Low Power Sensor

For Battery Powered Systems

- ▶ Compatible with Many Wireless Transmission Systems
  - ▶ Supply Voltage 3-5 Volts
  - ▶ 3 Pin MIL Connection or Integral Cable
- Note: Integral Cable Options are only for Permanent Monitoring Applications

### AC314-1A 3 Pin Connector


Connector Pin	Polarity
A	(+) Power
B	(-) Common
C	(+) Signal



Stock Product

### AC314-2C CB105 Integral Cable


Conductor	Polarity
Red	(+) Power
Black	(-) Common
White	(+) Signal



Built To Order

### AC314-3C CB218 Armored Integral Cable

Conductor	Polarity
Red	(+) Power
Black	(-) Common
White	(+) Signal



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC314	M/AC314	<b>Environmental</b>		
Sensitivity (±10%)		25 mV/g	Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	30-600,000 CPM	0,5-10000 Hz	Maximum Shock Protection		5,000 g, peak
Frequency Response (±10%)	60-480,000 CPM	1,0-8000 Hz	Sealing		IP68
Dynamic Range		± 50 g, peak	<b>Physical</b>		
<b>Electrical</b>			Sensing Element		PZT Ceramic
Settling Time		< 1 second	Sensing Structure		Shear Mode
Voltage Source (IEPE)		3-5 VDC (10%)	Weight	5.1 ounces	145 grams
Spectral Noise @ 10 Hz		60 µg/√Hz	Case Material		316L Stainless Steel
Spectral Noise @ 100 Hz		20 µg/√Hz	Connector (Non-Integral)		3 Pin MIL-C-5015
Spectral Noise @ 1000 Hz		5 µg/√Hz	Resonant Frequency	1,260,000 CPM	21000 Hz
Output Impedance		< 100 ohm	Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Bias Output Voltage		1.5 V ± 10%	Mounting Hardware Supplied	Captive Bolt	Captive Bolt
Case Isolation		> 10 <sup>8</sup> ohm	Calibration Certificate		CA10
Supply Current		< 20 µA			