

CL-50

Camera lens for BEAMAGE: 50 mm focal length.



PRODUCT FAMILY KEY FEATURES

MANAGE THE BEAM SIZE

A simple solution is offered to those who need to profile beams that are larger than the BEAMAGE sensor. This solution is a beam reducing optical component called CAMERA LENS.

IMAGE VERY LARGE BEAMS

The camera lenses in the CL series work by indirectly imaging the reflection or transmission of the beam after it has hit a diffusing element. For larger beams, simply increase the distance between the diffuser and the BEAMAGE.

READY TO USE WITHIN MINUTES

The CL series is C-mount threaded so you can mount it directly on the BEAMAGE camera

SPECIFICATIONS

MEASUREMENT CAPABILITIES	
Focal length	50 mm
Horizontal FOV	7°
FOV at 1 m	120 mm
Minimum working distance	1 m
Maximum beam size	Limited by field of view
Inverted image	Yes
Pixel multiplication factor (PMF)	Depends on set-up, auto-calibration routine available in the software
Damage thresholds	Very high because of indirect measurement
PHYSICAL CHARACTERISTICS	
Weight	0.225 kg
Mounting thread	C-Mount
ORDERING INFORMATION	
CL-50	202344

Specifications are subject to change without notice. Refer to the user manual for complete specifications.

INTERESTED IN THIS PRODUCT?

GET A QUOTE

Find your local sales representative at gentec-eo.com/contact-us