



## TMI110 Immersion Temperature Transmitter

		SPARE CODE		TMI110		1	2	3	4	5	6	7	8
hw	1 Output signals	<b>4...20 mA 2-Wire Loop Powered</b>											
		<b>Modbus RTU, RS 485</b>											
settings	2 Measured parameter for channel 1	<b>Temperature 0 ... +50°C (32 ... 122 °F)</b>											
		<b>Temperature -10 ... +40°C (14 ... 104 °F)</b>											
		<b>Temperature -40 ... +60°C (-40 ... 140 °F)</b>											
		<b>Temperature 0 ... +100°C (32 ... 212 °F)</b>											
		<b>Temperature Free scale °C</b>											
		<b>Temperature Free scale °F</b>											
hardware	5 Probe length	<b>Probe Length 100mm</b>											
		<i>Probe Length 150mm</i>											
		<i>Probe Length 200mm</i>											

**NOTE:** Selections in bold are included in the prices of the basic versions.  
• *Selections in italic are available at an extra price.*

**LINKS:** [User Guides](#)  
[Datasheet](#)  
[Vaisala.com product page](#)

Example of order code with typical settings:

	1	2	3	4	5	6	7	8
<b>TMI110</b>	<b>2</b>	<b>A</b>	<b>N</b>	<b>V</b>	<b>1</b>	<b>O</b>	<b>N</b>	<b>N</b>

**Related Items**  
Thermowell 100 mm, ISO 7 - R 1/2  
Thermowell 100 mm, 1/2 - 14 NPT

**Part number**  
ASM214691  
ASM214707